WORTHAM THEATER CENTER THE ALICE AND GEORGE BROWN THEATER

STAGE AND HOUSE INFORMATION

Seating Capacity	2465
Proscenium	30' h x 52' w
Tormentor Tower (adjustable)	58' - 38'
Main Stage depth	65' 6"
Rear Stage depth	42'
Apron depth (plaster line to apron edge)	6' 5"
Main Stage width (center line to stage left rail)	65' 4"
Main Stage width (center line to stage right sound door)	48'
Rear Stage width (center line to stage left rail)	52'
Rear Stage width (center line to stage right wall)	72'
Side Stage Right width (sound door to loading door)	57'
Side Stage Right depth	56'
Floor to Grid (subway grating - 3/4" opening)	89' h
Lighting Gallery Catwalk (SL / SR)	42' h
Hemp Gallery Catwalk (SL / SR)	68' h
House Curtain speed (motorized)	0 - 400' per minute
Fly Rail (combo hemp & synthetic)	Stage Left
Counterweight System (loft blocks overhead - clear grid floor)	97 sets (6" centers)
Arbor Capacity	1500 lbs
System Pipe length #1 - #4 (1-1/2" sch40)	65' 6" w
System Pipe length #5 - #97 (1-1/2" sch40)	61' 6" w (70' w/ Extensions)
Light Bridge	4' d x 39' w (52' w/ Extensions)
Motorized Sets (truss pipe)	14
Motor Set Capacity	1300 lbs
System Pipe trims	High - 83' Low - 4'
Counterweight	120,000 lbs (35's & 17.5's)
Counterweight (rear stage)	6000 lbs (35's & 17.5's)
Forestage Winch Sets	36' (1,500 lbs. cap.)
Freight Elevator (on loading dock)	12' w x 28' d
Clearance (off stage left & right and rear stage)	35'
Clearance (USR Arch)	24'
Stage Wagon (motorized)	60' w x 40' d x 20" h
Brown Theater Dock Door	20' x 20'
Exterior Dock Door (enclosed loading dock)	13' 10" h x 39' w
Loading Dock capacity (42" h w/ levelers)	Two Trailers
Power (offstage right - 100' from center line)	4 - 400 amp 3 ph disconnects
Power (loading dock)	2 - 200 amp 3 ph disconnects